

EA 5/3 GH

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER
5,5 KVA THREE-PHASE AND **2 KVA** SINGLE-PHASE /
 PETROL ENGINE **3000 GIRI/MIN**

Gen Set Features	<ul style="list-style-type: none"> + Low oil level cut out device + 1 x 16 A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker + 1 x 16 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + Earth Leakage Circuit Breaker (ELCB) 	
Gen Set Options (available as factory options)	<ul style="list-style-type: none"> + Versions with different voltages + 60 Hz version 	
Accessories on Request	+ Trolley	two-wheels and handles
Noise Level	+ LWA 95	(70 dB a 7m)
AC Generator 50 Hz	<ul style="list-style-type: none"> + Type synchronous + Three-phase p. (max.) 5,5 kVA - 400 V + Single-phase p. (max.) 2 kVA - 230 V + Power Factor 0,8 	
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> + Type Honda GX 270 OHV - 1 cil. 9 CV (6,6 kWm) - 270 cm³ + Fuel petrol + Cooling system air + Starting system manual recoil + Fuel tank capacity 6 l + Fuel consumption @ 75% 2,2 l/h 	
Other features	<ul style="list-style-type: none"> + Insulation Class H + Ambient temperature 40 °C + Altitude 1000 mt + Mechanical Protection IP 23 + Dimensions (L x W x H) 730 x 480 x 520 mm + Dry weight 80 kg 	

EA 5/3 GH

