

**THREE-PHASE POWER GENERATOR / OUTPUT POWERGRUPPO
11 KVA THREE-PHASE AND 4 KVA SINGLE-PHASE /
PETROL ENGINE 3000 RPM**

Gen Set Features	<ul style="list-style-type: none"> + Low oil level cut out device + 12 V built-in battery with electric start + 1 x 16 A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker + 1 x 16 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + Earth Leakage Circuit Breaker (ELCB) + Voltmeter + Hourmeter + Central lifting eye 	
Gen Set Options (available as factory options)	<ul style="list-style-type: none"> + Version with different voltages + 60 Hz version + AMF/ATS panel for auto start operation 	
Accessories on Request	<ul style="list-style-type: none"> + Trolley two-wheels and handles 	
Noise Level	<ul style="list-style-type: none"> + Lwa 98 (73 dB a 7 m) 	
AC Generator 50 Hz	<ul style="list-style-type: none"> + Type synchronous + Three-phase p. (stand-by) 11 kVA - 400 V + Three-phase p. (prime) 10 kVA - 400 V + Single-phase p.r (max.) 4 kVA - 230 V + Power Factor 0,8 	
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> + Type Honda GX 630 OHV - 2 cil. 14,1 CV (10,5 kWm) - 688 cm³ + Fuel Petrol + Cooling system air + Starting system electric + Fuel tank capacity 29 l + Fuel consumption @ 75% 6 l/h (@ 3600 rpm) 	
Other features	<ul style="list-style-type: none"> + Insulation Class H + Ambient temperature 40 °C + Altitude 1000 mt + Mechanical Protection IP 23 + Dimensions (L x W x H) 940 x 488 x 823 mm + Dry weight 148 kg 	

FX 12/4 GH